


Radiant and Luminous Intensity

Definition: The *radiant (luminous) intensity* is the power per unit solid angle from a point.

$$\frac{d\Phi}{d\Omega} = I(\omega)$$

$$\Phi = \int_{\Omega} I(\omega) d\Omega$$




$$\left[\frac{W}{sr} \right] \left[\text{candela} = cd = \frac{lm}{sr} \right]$$

CS348B Lecture 5

Pat Hanrahan, Spring 2000

The Invention of Photometry



Bouguer's Classic experiment
Compare two light sources
One is a candle

Definition of a standard candle

- Originally "standard" candle
- Currently
 550 nm laser with 1/683 W/sr

CS348B Lecture 5

Pat Hanrahan, Spring 2000

Luminance of Common Sources

Sky


Surface of the sun	2,000,000,000. cd/m ²
Sunlight clouds	30,000.
Clear day	3,000.
Overcast day	300.
Moonlight	0.03
Moonless	0.00003

Light Sources

Properties

- Spectral
 - Blackbody (incandescent)
 - Flourescent
- Point or area
- Directional distribution – goniometric diagram

Warn's Spotlight




$$\Phi = \int_0^{2p} \int_0^1 I(\mathbf{w}) d \cos \mathbf{q} d j = 2p \int_0^1 \cos^s \mathbf{q} d \cos \mathbf{q} = \frac{2p}{s+1}$$

$$I(\mathbf{w}) = \Phi \frac{s+1}{2p} \cos^s \mathbf{q}$$

CS348B Lecture 5

Pat Hanrahan, Spring 2000

Goniometric Diagrams



Isocandle diagram for
Novalux sodium luminaire

From Parry Moon
*The Scientific Basis of
Illuminating Engineering*
p. 236

CS348B Lecture 5

Pat Hanrahan, Spring 2000


Irradiance and Illuminance

Definition: The *irradiance (illuminance)* is the power per unit area incident on a surface.

$$dE(x) = L(\mathbf{w}_i) \cos \mathbf{q}_i d\mathbf{w}_i$$


$$E(x) = \int_{H^2} L(\mathbf{w}_i) \cos \mathbf{q}_i d\mathbf{w}$$

$$\left[\frac{W}{m^2} \right] \left[Lux = \frac{lm}{m^2} \right]$$




This is sometimes referred to as the radiant and luminous incidence.

Irradiance Distribution



Isolux contours

Isotropic Point Sources



$$I(\mathbf{w}) = \frac{\Phi}{4\mathbf{p}}$$


$$d\Phi = E dA = I d\mathbf{w} = \frac{\Phi}{4\mathbf{p}} \frac{\cos \mathbf{q}}{r^2} dA = \frac{\Phi}{4\mathbf{p}} \frac{\cos^3 \mathbf{q}}{h^2} dA$$

- Note inverse square law fall off.
- Note cosine dependency

CS348B Lecture 5

Pat Hanrahan, Spring 2000

Distant Source




$$E = E_s \cos q_s$$

CS348B Lecture 5

Pat Hanrahan, Spring 2000

Hemisphere: Projected Solid Angle




$$\int_{\Omega} \cos \theta \, d\Omega = p$$

CS348B Lecture 5

Pat Hanrahan, Spring 2000

Disk




$$\begin{aligned} E &= \int_0^{\cos \theta_d} \int_0^{2p} L \cos \theta \, df \, d \cos \theta \\ &= 2pL \frac{\cos^2 \theta}{2} \Big|_0^{\cos \theta_d} \\ &= Lp \sin^2 \theta_d \\ &= Lp \frac{r^2}{r^2 + R^2} \end{aligned}$$

CS348B Lecture 5

Pat Hanrahan, Spring 2000

Sphere



$$\begin{aligned} E &= \int L \cos q \, d\omega \\ &= L p \sin^2 q \\ &= L p \frac{r^2}{R^2} \end{aligned}$$

CS348B Lecture 5

Pat Hanrahan, Spring 2000

The Sun

Solar constant (normal incidence at zenith)

Irradiance 1353 W/m²

Illuminance 127,500 Lumen/m² = 127.5 Kilo-Lux

Solar angle

$a = .25$ degrees = .004 radians (half angle)

$w = p \sin^2 a = 6 \times 10^{-5}$ steradians

Radiance

$$L = \frac{E}{w} = \frac{1.353 \times 10^3 \text{ W/m}^2}{6 \times 10^{-5} \text{ sr}} = 2.25 \times 10^7 \frac{\text{W}}{\text{m}^2 \cdot \text{sr}}$$


Pluto (6 tera-meters) 50 Lux - read a newspaper

Deep space -> 20 micro-lux (see, but not read!)

CS348B Lecture 5

Pat Hanrahan, Spring 2000



Polygonal Source



CS348B Lecture 5

Pat Hanrahan, Spring 2000

Lambert's Formula




$$\sum_{i=1}^n A_i = \sum_{i=1}^n g_i \vec{N} \cdot \vec{N}_i$$

CS348B Lecture 5

Pat Hanrahan, Spring 2000

Form Factor



$$d\mathbf{w} = \frac{\cos \mathbf{q}'}{\|x - x'\|^2} dA'$$

$$\cos \mathbf{q} d\mathbf{w} = \frac{\cos \mathbf{q} \cos \mathbf{q}'}{\|x - x'\|^2} dA'$$

$$T = \iint_{A A'} \frac{\cos \mathbf{q}' \cos \mathbf{q}}{\mathbf{p} \|x - x'\|^2} dA' dA$$

CS348B Lecture 5

Pat Hanrahan, Spring 2000

Form Factors

Differential-differential $F_{dA_i, dA_j} = \frac{\cos \mathbf{q}'_o \cos \mathbf{q}_i}{\mathbf{p} \|x - x'\|^2} dA_j$

Differential-finite $F_{dA_i, A_j} = \int_{A_j} \frac{\cos \mathbf{q}'_o \cos \mathbf{q}_i}{\mathbf{p} \|x - x'\|^2} dA'$

Finite-finite $F_{A_i, A_j} = \frac{1}{A_i} \int_{A_i} \int_{A_j} \frac{\cos \mathbf{q}'_o \cos \mathbf{q}_i}{\mathbf{p} \|x - x'\|^2} dA' dA$

CS348B Lecture 5

Pat Hanrahan, Spring 2000

Form Factor Properties

Form factor is the percentage of light transferred between surfaces

1. Reciprocity

$$T_{ij} = A_i F_{ij} = \int_{A_i} \int_{A_j} \frac{\cos \mathbf{q}'_o \cos \mathbf{q}_i}{\mathbf{p} \|x - x'\|^2} dA' dA = T_{ji} = A_j F_{ji}$$

2. Summation


$$\sum_j F_{ij} = \sum_i F_{ji} = 1$$

CS348B Lecture 5

Pat Hanrahan, Spring 2000

Radiosity and Luminosity

Definition: The *radiosity (luminosity)* is the energy per unit area leaving a surface.



$$B(x) = \int_{H^2} L(\mathbf{w}_o) \cos \mathbf{q}_o d\mathbf{w}_o$$

$$\left[\frac{W}{m^2} \right] \left[Lux = \frac{lm}{m^2} \right]$$

This is officially referred to as the radiant and luminous exitance.

CS348B Lecture 5

Pat Hanrahan, Spring 2000

Uniform Diffuse Source

$$\begin{aligned}
 B &= \int L \cos \mathbf{q} \, d\mathbf{w} \\
 &= L \int \cos \mathbf{q} \, d\mathbf{w} \\
 &= \mathbf{p}L
 \end{aligned}
 \qquad
 L = \frac{B}{\mathbf{p}}$$

blondel = *apostilb* = $\frac{1}{\mathbf{p}} \text{ nit} = \frac{1}{\mathbf{p}} \text{ cd} / \text{m}^2$ (*skot* = 10^{-3} *apostilb*)

lamberts = $\frac{1}{\mathbf{p}} \text{ cd} / \text{cm}^2$

foot-lamberts = $\frac{1}{\mathbf{p}} \text{ cd} / \text{ft}^2$ (*glim* = 10^{-3} *foot-lambert*)

Radiometric and Photometric Terms

Physics	Radiometry	Photometry
Energy	Radiant Energy	Luminous Energy
Flux (Power)	Radiant Power	Luminous Power
Flux Density	Irradiance	Illuminance
	Radiosity	Luminosity
Angular Flux Density	Radiance	Luminance
Intensity	Radiant Intensity	Luminous Intensity

Photometric Units

Photometry	Units		
	MKS	CGS	British
Luminous Energy	Talbot		
Luminous Power	Lumen		
Illuminance	Lux	Phot	Footcandle
Luminosity			
Luminance	Nit	Stilb	
	Apostilb, Blondell	Lambert	Footlambert
Luminous Intensity	Candela (Candle, Candlepower, Carcel, Hefner)		

" Thus one nit is one lux per steradian is one candela per square meter is one lumen per square meter per steradian. Got it?" *Kajiya*